

Crimping Pump
ELECTRIC HYDRAULIC PE-NUT

0,49 l/min
Two-Speed

Extremely durable yet lightweight
and operate under low-line
voltage conditions.

PUMPS

PE-NUT PUMP – 115V

- 0,46 KW universal electric motor (50 cycle)
- Two-stage pump for rapid ram advance
- Operational under low-line voltage conditions
- Optional operating pressures available; consult Power Team for details
- Designed for use with spring-returned remote tools
- High-pressure safety relief valve
- Remote hand control with 3,1 m cord
- Carrying handle
- Factory filled oil reservoir
- Pressure matched quick-coupler supplied
- Optional carrying case
- Two-stage pumping system
- Unique, intermittent duty pump
- Piston-type high-pressure pump supercharged by a low-pressure pump.



⚠ CAUTION: DESIGNED FOR CRIMPING APPLICATIONS ONLY! This system should not be used for lifting.

| Order No. | Oil Delivery (l/min.) | Oil Reservoir qt. (l) | Usable Oil qt. (l) | Overall Width (mm) | Overall Length (mm) | Overall Depth (mm) | Pump Weight w/Oil (kg) |
|-----------|-----------------------|-----------------------|--------------------|--------------------|---------------------|--------------------|------------------------|
| PE-NUT | 2,62 at 7 bar | 6 | 2,8 | 165 | 365 | 210 | 12,6 |
| PE-NUTC* | 0,49 at 700 bar | | | | | | |

*Includes Case

| Electric Motor | Electrical Data | Electrical Control |
|--|-----------------|--------------------|
| 0,46 KW, 10,000 rpm 115V AC, 50 Hz 11 amp current draw (115V at 700 bar) | | |

GASOLINE POWER PUMPS

- PG1203-CP
- 4,5 Kw Briggs & Stratton engine
 - Manual control valve
 - High-pressure safety relief valve
 - Protective roll cage
 - For use with single acting tools

PG1203/4S-CP

- 4,1 Kw Honda OHV-type engine
- Remote hand control with 3,1 m cord
- Two-stage pump for rapid advance
- High-pressure safety relief valve
- Protective roll cage
- For use with either single or double acting tools



⚠ CAUTION: DESIGNED FOR CRIMPING APPLICATIONS ONLY! This system should not be used for lifting.

| Order No. | Oil Delivery (l/min.) | Oil Reservoir (l) | Usable Oil (l) | Overall Width (mm) | Overall Length (mm) | Overall Height (mm) | Pump Weight w/Oil (kg) |
|--------------|-----------------------|-------------------|----------------|--------------------|---------------------|---------------------|------------------------|
| PG1203-CP | 8 at 7 bar | 11,3 | 7 | 502 | 552 | 622 | 25 |
| PG1203/4S-CP | 2,1 at 700 bar | | | | | | |



Crimping Pump
GAS HYDRAULIC PG120

Crimping Pump
2,1 l/min
Two-Speed

Two-stage pump for rapid
advance

PUMPS