



Standart Seri Havalı Tork Anahtarları

Standard Series Pneumatic Torque Multipliers



- » Cihaz kapasitesinin %20-%100 aralığında ± 5 hassasiyet.
- » Fabrika çıkışlı, seri numaralı izlenebilir kalibrasyon belgesi.
- » 100 ile 6.000 N.m arasında on farklı model.
- » Dakikada 224 rpm'e kadar boşta dönüş hızı.
- » Saniyede 19 litre hava tüketimi, 6.3 bar çalışma basıncı.
- » Darbesiz, sessiz, çalışma gürültüsü 85 dB(A) altındadır.
- » Yön mandalı ile sıkma ve sökme yönüne kolayca geçiş sağlar.

- » ± 5 repeatability of reading from 20% to 100% of range.
- » Serial number and calibration certificate for each tool.
- » Ten different model options from 100 - 6.000 N.m.
- » Maximum idle speed 224 rpm.
- » Maximum working pressure 6.3 bar, air consumption 19 litres/sec.
- » Quiet - less than 85 dB(A) when under load.
- » Easily accessible switch for forward and reverse operation.

Parça Part	Kapasite Capacity		Şanzıman Çapı Gear Dia. (ØD)	Sürücü Sq. Drive	Devir Hızı Idle Speed	Ağırlık Weight	D	H1	H2	H3	L	R1	R2 min	R2 max
No.	N.m	Lbf.ft	mm	inç	d/d (rpm)	kg	mm							
18100.B06	100 - 500	74 - 370	52	3/4"	224	4.95	52	29	224	116	310	59	71	131
18101.B06	160 - 800	118 - 590	52	3/4"	148	4.95	52	29	224	116	310	59	71	131
18102.B06	200 - 1.000	147 - 738	72	3/4"	122	6.8	72	29	224	116	342	68	91	165
18103.B08	270 - 1.350	200 - 1.000	72	1"	86	6.8	72	29	224	116	342	68	91	165
18104.B08	400 - 2.000	295 - 1.475	72	1"	58	7.2	72	29	224	116	371	74	91	165
18106.B08	540 - 2.700	400 - 2.000	92	1"	46	9.85	92	29	224	116	394	87	115	205
18119.B08	800 - 4.000	590 - 2.950	92	1"	32	9.85	92	29	224	116	394	87	115	205
18119.B12	800 - 4.000	590 - 2.950	92	1.1/2"	32	9.85	92	29	224	116	394	84	115	205
18108.B12	900 - 4.500	660 - 3.300	119	1.1/2"	23	14.6	119	29	224	116	415	118	150	199
18109.B12	1.200 - 6.000	885 - 4.500	119	1.1/2"	15.5	14.6	119	29	224	116	415	118	150	199

