



Standart Seri Açılı Tip Havalı Tork Anahtarları

Standard Series Right Angle Gearbox Pneumatic Torque Multipliers



- » Cihaz kapasitesinin %20-%100 aralığında \pm %5 hassasiyet.
- » 90° açılı formu ile dar bölgeler için ideal çözüm sunar.
- » Fabrika çıkışlı, seri numaralı izlenebilir kalibrasyon belgesi.
- » 100 ile 6.000 N.m arasında on farklı model.
- » Dakikada 224 rpm'e kadar boşta dönüş hızı.
- » Saniyede 19 litre hava tüketimi, 6.3 bar çalışma basıncı.
- » Darbesiz, sessiz, çalışma gürültüsü 85 dB(A) altındadır.
- » Yön mandalı ile sıkma ve sökme yönüne kolayca geçiş sağlar.

- » \pm %5 repeatability of reading from 20% to 100% of range.
- » 90° angled form provides the ideal solution for narrow areas.
- » Serial number and calibration certificate for each tool.
- » Ten different model options from 100 - 6.000 N.m.
- » Maximum idle speed 224 rpm.
- » Maximum working pressure 6.3 bar, air consumption 19 litres/sec.
- » Quiet - less than 85 dB(A) when under load.
- » Easily accessible switch for forward and reverse operation.

Parça Part	Kapasite Capacity		Sürücü Sq. Drive	Devir Hızı Idle Speed	Ağırlık Weight	D	H1	H2	H3	H4	H5	L1	L2	R1	R2 min	R2 max	W
No.	N.m	Lbf.ft	inç	d/d (rpm)	kg	mm											
18100.B06.RA	100 - 500	74 - 370	3/4"	224	7.11	52	166	28	224	29	116	307	272	59	71	131	82
18101.B06.RA	160 - 800	118 - 590	3/4"	148	7.11	52	166	28	224	29	116	307	272	59	71	131	82
18102.B06.RA	200 - 1.000	147 - 738	3/4"	122	8.96	72	198	28	224	29	116	307	272	74	91	166	82
18103.B08.RA	270 - 1.350	200 - 1.000	1"	86	8.96	72	198	28	224	29	116	307	272	74	91	166	82
18104.B08.RA	400 - 2.000	295 - 1.475	1"	58	9.36	72	226	28	224	29	116	307	272	74	91	166	82
18106.B08.RA	540 - 2.700	400 - 2.000	1"	46	12.01	92	250	28	224	29	116	307	272	87	124	205	82
18119.B08.RA	800 - 4.000	590 - 2.950	1"	32	12.01	92	250	28	224	29	116	307	272	87	124	205	82
18119.B12.RA	800 - 4.000	590 - 2.950	1.1/2"	32	12.01	92	250	28	224	29	116	307	272	87	124	205	82
18108.B12.RA	900 - 4.500	660 - 3.300	1.1/2"	23	17.56	119	272	28	224	29	116	307	272	119	149	199	82
18109.B12.RA	1.200 - 6.000	885 - 4.500	1.1/2"	15.5	17.56	119	272	28	224	29	116	307	272	119	149	199	82

