



Standart Havalı Bijon Tork Anahtarları

Standard Series Truck and Bus Wheel Pneumatic Torque Multipliers



- » Cihaz kapasitesinin %20-%100 aralığında ± 5 hassasiyet.
 - » Fabrika çıkışlı, seri numaralı izlenebilir kalibrasyon belgesi.
 - » Dakikada 122 rpm'e kadar boşa dönüş hızı.
 - » Saniyede 19 litre hava tüketimi, 6.3 bar çalışma basıncı.
 - » Uzun ömürlü sağlam ve hafif yapı, hızlı ve kolay kullanım.
 - » Sabit destek ayağı ile güvenli çalışma imkanı.
 - » Darbesiz, sessiz, çalışma gürültüsü 85 dB(A) altındadır.
-
- » ± 5 repeatability of reading from 20% to 100% of range.
 - » Serial number and calibration certificate for each tool.
 - » Maximum idle speed 122 rpm.
 - » Maximum working pressure 6.3 bar, air consumption 19 litres/sec.
 - » Robust and lightweight, quick and easy to operate
 - » Extended reaction is ideal for reaching recessed nuts.
 - » Quiet - less than 85 dB(A) when under load.

Parça Part	Kapasite Capacity		Sürücü Sq. Drive	Devir Hızı Idle Speed	Ağırlık Weight	D	H1	H2	H3	L	R1	R2 min	R2 max
No.	N.m	Lbf.ft	inç	d/d (rpm)	kg	mm							
18140.B06	200 - 1.000	147 - 738	3/4"	122	7.2	72	29	224	116	403	81	63	110
18149.B08	200 - 1.000	147 - 738	1"	122	7.2	72	29	224	116	403	81	63	110
18141.B08	400 - 2.000	295 - 1.475	1"	58	7.7	72	29	224	116	458	49	63	115
Dahili Kontrollü Dijital Modeller / Internal Control Digital Models ± 2 Hassasiyet / Accuracy													
18142.B06	200 - 1.000	147 - 738	3/4"	122	8.5	72	29	224	116	403	81	63	110
18143.B08	400 - 2.000	295 - 1.475	1"	58	9	72	29	224	116	458	49	63	115
Dahili Kontrollü Dijital Modeller / External Control Digital Models ± 2 Hassasiyet / Accuracy													
18144.B06	200 - 1.000	147 - 738	3/4"	122	8.5	72	29	224	116	403	81	63	110
18145.B08	400 - 2.000	295 - 1.475	1"	58	9	72	29	224	116	458	49	63	115

